

PTP 820S Licensed Microwave Radio



All-Outdoor

Specifications

RADIO

- 6-38 GHz
- 1+0, 1+1 HSB, 2+0 SP or DP
- Multi-Band (PTP 850E, PTP 820E)

Radio Features

- Protection: 1+1 HSB
- QPSK to 2048 QAM w/ACM
- Advanced Frequency Reuse (AFR)

ETHERNET

Ethernet Interfaces

- Traffic Interfaces – 1 x 10/100/1000Base-T (RJ-45) and 2 x 1000base-X (SFP) or 2 x 10/100/1000 Base-T (electrical SFP)
- Management Interface - 1 x 10/100 Base-T (RJ-45)
- Optical SFP Types - Optical 1000Base-LX (1310 nm) or SX (850nm)
Note: SFP devices must be of industrial grade (-40°C to +85°C)

Ethernet Features

- MTU – 9600 Bytes
- Quality of Service
 - Multiple Classification criteria (VLAN ID, p-bits, IPv4, DSCP, IPv6 TC, MPLS EXP)
 - 8 priority queues
 - Deep buffering (configurable up to 64 Mbit per queue)
 - WRED
 - P-bit marking/remarking
- 4K VLANs
- VLAN add/remove/translate

- Frame Cut Through – controlled latency and PDV for delay sensitive applications
- Header De-Duplication – Capacity boosting by eliminating inefficiency in all layers (L2, MPLS, L3, L4, Tunneling – GTP for LTE, GRE)
- Y.1731 Ethernet OAM
- Y.1731 Ethernet Bandwidth Notification (ETH-BN)
- Adaptive Bandwidth Notification (ABN)

MANAGEMENT PROTOCOL

- SNMP
- REST
- SDN Support: NETCONF/YANG

SYNCHRONIZATION

Synchronization Distribution

- Sync Distribution over any traffic interface (GE/FE)
- Sync-E (ITU-T G.8261, G.8262)
- SSM/ESMC Support for ring/mesh applications (ITU-T G.8264)
- Sync-E Regenerator mode, providing PRC grade (ITU-T G.811) performance for smart pipe applications.

IEEE-1588

- Optimized Transport for reduced PDV
- IEEE-1588 TC

STANDARD

MEF

- Carrier Ethernet 2.0

Supported Ethernet Standards

- 10/100/1000base-T/X (IEEE 802.3)
- Ethernet VLANs (IEEE 802.3ac)
- Virtual LAN (VLAN, IEEE 802.1Q)
- Class of service (IEEE 802.1p)
- Provider bridges (QinQ – IEEE 802.1ad)
- Link aggregation (IEEE 802.3ad)
- Auto MDI/MDIX for 1000baseT
- RFC 1349: IPv4 TOS
- RFC 2474: IPv4 DSCP
- RFC 2460: IPv6 Traffic Classes

Security

- AES 256-bit Encryption
- Secured protocols (HTTPS, SNMPV3, SSH, SFTP)
- Radius authentication and authorization
- TACACS+ authentication and authorization (session-based)

Standards Compliance

- EMC: EN 301 489-1, EN 301 489-4, Class B (Europe), FCC 47 CFR, part 15, class B (US), ICES-003, Class B (Canada), TEC/EMI/TEL-001/01, Class B (India)
- Surge: EN61000-4-5, Class 4 (for PWR and ETH1/PoE ports)
- Safety: EN 60950-1, IEC 60950-1, UL 60950-1, CSA-C22.2 No.60950-1, EN 60950-22, UL 60950-22, CSAC22.2.60950-22

- Ingress Protection: IP66-compliant
- Storage: ETSI EN 300 019-1-1 Class 1.2
- Transportation: ETSI EN 300 019-1-2 Class 2.3

TECHNICAL SPECIFICATION

Mechanical Specifications

- Dimensions: 230mm(H), 233mm(W), 98mm(D), 6.0kg;

9.05”(H), 9.07”(W), 3.86”(D), 13.23 lbs.

- Pole Diameter Range (for Remote Mount Installation): 8.89 cm – 11.43 cm; 3.5” – 4.5”

Environmental Specifications

- -33°C to +55°C (-45°C to +60°C extended); -27°F to +131°F (-49°F to +140°F extended)

PTP 820S SPECIFICATION SHEET

Power Input Specifications

- Standard Input: -48 VDC
- IDU DC Input range: -40 to -60 VDC

Power Consumption Specifications

- Maximum Power Consumption: 6-11 GHz: 35W; 13-38 GHz: 42W

Specifications

TRANSMIT POWER

Transmit Power (dBm)	Frequency (GHz)									
	6	7	8	10-11	13-15	18	23	24 UL HP	26	28-38
QPSK	28	28	28	26	24	22	20	0	21	18
8 PSK	28	28	28	26	24	22	20	0	21	18
16 QAM	28	27	27	26	23	21	20	0	20	17
32 QAM	27	26	26	25	22	20	20	0	19	16
64 QAM	27	26	26	25	22	20	20	0	19	16
128 QAM	27	26	26	25	22	20	20	0	19	16
256 QAM	27	26	24	25	20	20	18	0	17	14
512 QAM	25	24	24	24	20	18	18	0	17	14
1024 QAM	25	24	24	23	20	18	17	0	16	13
2048 QAM	23	22	22	21	18	16	16	0	15	12

RECEIVE SENSITIVITY

Modulation	Channel Size	Frequency (GHz)													
		6	7	8	10	11	13	15	18	23	24	26	28-31	32	38
QPSK	3.5 & 5 MHz	-96.5	-96.0	-96.0	-95.5	-96.5	-95.5	-94.5	-96.0	-95.0	-94.5	-94.5	-94.5	-94.0	-94.0
16 QAM		-90.0	-89.0	-89.0	-89.0	-89.5	-88.5	-88.0	-89.0	-88.0	-87.5	-88.0	-87.5	-87.5	-87.0
32 QAM		-86.5	-85.5	-85.5	-85.5	-86.0	-85.0	-84.5	-85.5	-84.5	-84.0	-84.5	-84.0	-84.0	-83.5
64 QAM		-83.0	-82.5	-82.5	-82.0	-83.0	-82.0	-81.0	-82.5	-81.5	-81.0	-81.0	-81.0	-80.5	-80.5
128 QAM		-79.5	-79.0	-79.0	-78.5	-79.5	-78.5	-77.5	-79.0	-78.0	-77.5	-77.5	-77.5	-77.0	-77.0
256 QAM		-76.5	-75.5	-75.5	-75.5	-76.5	-75.0	-74.5	-75.5	-75.0	-74.5	-74.5	-74.0	-74.0	-73.5
QPSK	7 MHz	-93.5	-93.0	-93.0	-92.5	-93.5	-92.5	-91.5	-93.0	-92.0	-91.5	-91.5	-91.5	-91.0	-91.0
8 PSK		-87.5	-87.0	-87.0	-86.5	-87.5	-86.5	-85.5	-87.0	-86.0	-85.5	-85.5	-85.5	-85.0	-85.0
16 QAM		-87.0	-86.5	-86.5	-86.0	-87.0	-86.0	-85.0	-86.5	-85.5	-85.0	-85.0	-85.0	-84.5	-84.5
32 QAM		-83.5	-83.0	-83.0	-82.5	-83.5	-82.5	-81.5	-83.0	-82.0	-81.5	-81.5	-81.5	-81.0	-81.0
64 QAM		-80.5	-80.0	-80.0	-79.5	-80.5	-79.5	-78.5	-80.0	-79.0	-78.5	-78.5	-78.5	-78.0	-78.0
128 QAM		-77.5	-76.5	-76.5	-76.5	-77.5	-76.0	-75.5	-76.5	-76.0	-75.5	-75.5	-75.0	-75.0	-74.5
256 QAM		-74.0	-73.5	-73.5	-73.0	-74.0	-73.0	-72.0	-73.5	-72.5	-72.0	-72.0	-72.0	-71.5	-71.5
512 QAM		-72.0	-71.5	-71.5	-71.0	-72.0	-71.0	-70.0	-71.5	-70.5	-70.0	-70.0	-70.0	-69.5	-69.5
1024 QAM (strong FEC)		-68.5	-68.0	-68.0	-67.5	-68.5	-67.5	-66.5	-68.0	-67.0	-66.5	-66.5	-66.5	-66.0	-66.0
1024 QAM (light FEC)		-68.0	-67.0	-67.0	-67.0	-67.5	-66.5	-66.0	-67.0	-66.0	-65.5	-66.0	-65.5	-65.5	-65.0
QPSK	10 MHz	-92.0	-91.5	-91.5	-91.0	-92.0	-91.0	-90.0	-91.5	-90.5	-87.0	-90.0	-90.0	-89.5	-89.0
8 PSK		-87.0	-86.0	-86.0	-86.0	-87.0	-85.5	-85.0	-86.0	-85.5	-81.5	-85.0	-84.5	-84.5	-84.0
16 QAM		-85.5	-85.0	-85.0	-84.5	-85.5	-84.5	-83.5	-85.0	-84.0	-80.5	-83.5	-83.5	-83.0	-82.5
32 QAM		-82.0	-81.5	-81.5	-81.0	-82.0	-81.0	-80.0	-81.5	-80.5	-77.0	-80.0	-80.0	-79.5	-79.0
64 QAM		-79.0	-78.5	-78.5	-78.0	-79.0	-77.5	-77.0	-78.5	-77.5	-74.0	-77.0	-77.0	-76.5	-76.0
128 QAM		-75.5	-75.0	-75.0	-74.5	-75.5	-74.5	-73.5	-75.0	-74.0	-70.5	-73.5	-73.5	-73.0	-72.5
256 QAM		-72.5	-72.0	-72.0	-71.5	-72.5	-71.5	-70.5	-72.0	-71.0	-67.5	-70.5	-70.5	-70.0	-69.5
512 QAM		-70.0	-69.5	-69.5	-69.0	-70.0	-68.5	-68.0	-69.5	-68.5	-65.0	-68.0	-68.0	-67.5	-67.0
1024 QAM (strong FEC)		-67.0	-66.5	-66.5	-66.0	-67.0	-66.0	-65.0	-66.5	-65.5	-62.0	-65.0	-65.0	-64.5	-64.0
1024 QAM (light FEC)		-66.5	-65.5	-65.5	-65.5	-66.5	-65.0	-64.5	-65.5	-65.0	-61.0	-64.5	-64.0	-64.0	-63.5
QPSK	14 MHz	-90.5	-90.0	-90.0	-89.5	-90.5	-89.5	-88.5	-90.0	-89.0	-88.5	-88.5	-88.5	-88.0	-88.0
8 PSK		-84.5	-84.0	-84.0	-83.5	-84.5	-83.5	-82.5	-84.0	-83.0	-82.5	-82.5	-82.5	-82.0	-82.0
16 QAM		-83.5	-83.0	-83.0	-82.5	-83.5	-82.5	-81.5	-83.0	-82.0	-81.5	-81.5	-81.5	-81.0	-81.0
32 QAM		-80.5	-79.5	-79.5	-79.5	-80.5	-79.0	-78.5	-79.5	-79.0	-78.5	-78.5	-78.0	-78.0	-77.5
64 QAM		-77.5	-76.5	-76.5	-76.5	-77.5	-76.0	-75.5	-76.5	-76.0	-75.5	-75.5	-75.0	-75.0	-74.5
128 QAM		-74.0	-73.5	-73.5	-73.0	-74.0	-73.0	-72.0	-73.5	-72.5	-72.0	-72.0	-72.0	-71.5	-71.5
256 QAM		-71.5	-70.5	-70.5	-70.5	-71.0	-70.0	-69.5	-70.5	-69.5	-69.0	-69.5	-69.0	-69.0	-68.5
512 QAM		-68.5	-68.0	-68.0	-67.5	-68.5	-67.5	-66.5	-68.0	-67.0	-66.5	-66.5	-66.5	-66.0	-66.0
1024 QAM (strong FEC)		-65.5	-65.0	-65.0	-64.5	-65.5	-64.5	-63.5	-65.0	-64.0	-63.5	-63.5	-63.5	-63.0	-63.0
1024 QAM (light FEC)		-65.0	-64.0	-64.0	-64.0	-65.0	-63.5	-63.0	-64.0	-63.5	-63.0	-63.0	-62.5	-62.5	-62.0

PTP 820C SPECIFICATION SHEET

Modulation	Channel Size	Frequency (GHz)													
		6	7	8	10	11	13	15	18	23	24	26	28-31	32	38
QPSK	20 MHz	-89.0	-88.5	-88.5	-88.0	-89.0	-88.0	-87.0	-88.5	-87.5	-84.0	-87.0	-87.0	-86.5	-86.0
8 PSK		-84.0	-83.5	-83.5	-83.0	-84.0	-83.0	-82.0	-83.5	-82.5	-79.0	-82.0	-82.0	-81.5	-81.0
16 QAM		-82.5	-82.0	-82.0	-81.5	-82.5	-81.0	-80.5	-82.0	-81.0	-77.5	-80.5	-80.5	-80.0	-79.5
32 QAM		-79.0	-78.5	-78.5	-78.0	-79.0	-77.5	-77.0	-78.5	-77.5	-74.0	-77.0	-77.0	-76.5	-76.0
64 QAM		-76.0	-75.0	-75.0	-75.0	-76.0	-74.5	-74.0	-75.0	-74.5	-70.5	-74.0	-73.5	-73.5	-73.0
128 QAM		-73.0	-72.0	-72.0	-72.0	-73.0	-71.5	-71.0	-72.0	-71.5	-67.5	-71.0	-70.5	-70.5	-70.0
256 QAM		-70.0	-69.5	-69.5	-69.0	-70.0	-68.5	-68.0	-69.5	-68.5	-65.0	-68.0	-68.0	-67.5	-67.0
512 QAM		-67.5	-66.5	-66.5	-66.5	-67.5	-66.0	-65.5	-66.5	-66.0	-62.0	-65.5	-65.0	-65.0	-64.5
1024 QAM (strong FEC)		-64.5	-63.5	-63.5	-63.5	-64.5	-63.0	-62.5	-63.5	-63.0	-59.0	-62.5	-62.0	-62.0	-61.5
1024 QAM (light FEC)		-63.5	-63.0	-63.0	-62.5	-63.5	-62.5	-61.5	-63.0	-62.0	-58.5	-61.5	-61.5	-61.0	-60.5
2048 QAM		-60.0	-59.5	-59.5	-59.0	-60.0	-59.0	-58.0	-59.5	-58.5	-55.0	-58.0	-58.0	-57.5	-57.0
QPSK	25MHz	-87.5	-86.5	-86.5	-86.5	-87.0	-86.0	-85.5	-86.5	-85.5	-82.0	-85.5	-85.0	-85.0	-84.0
8 PSK		-82.5	-82.0	-82.0	-81.5	-82.5	-81.5	-80.5	-82.0	-81.0	-77.5	-80.5	-80.5	-80.0	-79.5
16 QAM		-80.5	-80.0	-80.0	-79.5	-80.5	-79.5	-78.5	-80.0	-79.0	-75.5	-78.5	-78.5	-78.0	-77.5
32 QAM		-77.5	-77.0	-77.0	-76.5	-77.5	-76.0	-75.5	-77.0	-76.0	-72.5	-75.5	-75.5	-75.0	-74.5
64 QAM		-74.5	-74.0	-74.0	-73.5	-74.5	-73.5	-72.5	-74.0	-73.0	-69.5	-72.5	-72.5	-72.0	-71.5
128 QAM		-71.5	-71.0	-71.0	-70.5	-71.5	-70.5	-69.5	-71.0	-70.0	-66.5	-69.5	-69.5	-69.0	-68.5
256 QAM		-68.5	-67.5	-67.5	-67.5	-68.5	-67.0	-66.5	-67.5	-67.0	-63.0	-66.5	-66.0	-66.0	-65.5
512 QAM		-66.0	-65.0	-65.0	-65.0	-66.0	-64.5	-64.0	-65.0	-64.5	-60.5	-64.0	-63.5	-63.5	-63.0
1024 QAM (strong FEC)		-63.0	-62.5	-62.5	-62.0	-63.0	-61.5	-61.0	-62.5	-61.5	-58.0	-61.0	-61.0	-60.5	-60.0
1024 QAM (light FEC)		-62.5	-61.5	-61.5	-61.5	-62.5	-61.0	-60.5	-61.5	-61.0	-57.0	-60.5	-60.0	-60.0	-59.5
2048 QAM		-58.5	-58.0	-58.0	-57.5	-58.5	-57.0	-56.5	-58.0	-57.0	-53.5	-56.5	-56.5	-56.0	-55.5
QPSK	28 MHz	-87.5	-87.0	-87.0	-86.5	-87.5	-86.5	-85.5	-87.0	-86.0	-85.5	-85.5	-85.5	-85.0	-85.0
8 PSK		-83.0	-82.5	-82.5	-82.0	-83.0	-82.0	-81.0	-82.5	-81.5	-81.0	-81.0	-81.0	-80.5	-80.5
16 QAM		-81.0	-80.5	-80.5	-80.0	-81.0	-79.5	-79.0	-80.5	-79.5	-79.0	-79.0	-79.0	-78.5	-78.0
32 QAM		-77.5	-77.0	-77.0	-76.5	-77.5	-76.0	-75.5	-77.0	-76.0	-75.5	-75.5	-75.5	-75.0	-74.5
64 QAM		-74.5	-74.0	-74.0	-73.5	-74.5	-73.0	-72.5	-74.0	-73.0	-72.5	-72.5	-72.5	-72.0	-71.5
128 QAM		-71.5	-70.5	-70.5	-70.5	-71.0	-70.0	-69.5	-70.5	-69.5	-69.0	-69.5	-69.0	-69.0	-68.5
256 QAM		-68.5	-67.5	-67.5	-67.5	-68.0	-67.0	-66.5	-67.5	-66.5	-66.0	-66.5	-66.0	-66.0	-65.5
512 QAM		-66.0	-65.0	-65.0	-65.0	-66.0	-64.5	-64.0	-65.0	-64.5	-64.0	-64.0	-63.5	-63.5	-63.0
1024 QAM (strong FEC)		-63.0	-62.5	-62.5	-62.0	-63.0	-61.5	-61.0	-62.5	-61.5	-61.0	-61.0	-61.0	-60.5	-60.0
1024 QAM (light FEC)		-62.0	-61.5	-61.5	-61.0	-62.0	-60.5	-60.0	-61.5	-60.5	-60.0	-60.0	-60.0	-59.5	-59.0
2048 QAM		-58.5	-58.0	-58.0	-57.5	-58.5	-57.0	-56.5	-58.0	-57.0	-56.5	-56.5	-56.5	-56.0	-55.5
QPSK	30 MHz	-87.5	-87.0	-87.0	-86.5	-87.5	-86.0	-85.5	-87.0	-86.0	-85.5	-85.5	-85.5	-85.0	-84.5
8 PSK		-82.5	-81.5	-81.5	-81.5	-82.5	-81.0	-80.5	-81.5	-81.0	-80.5	-80.5	-80.0	-80.0	-79.0
16 QAM		-81.0	-80.0	-80.0	-80.0	-80.5	-79.5	-79.0	-80.0	-79.0	-78.5	-79.0	-78.5	-78.5	-77.5
32 QAM		-77.0	-76.5	-76.5	-76.0	-77.0	-76.0	-75.0	-76.5	-75.5	-75.0	-75.0	-75.0	-74.5	-74.0
64 QAM		-74.5	-73.5	-73.5	-73.5	-74.0	-73.0	-72.5	-73.5	-72.5	-72.0	-72.5	-72.0	-72.0	-71.0
128 QAM		-71.0	-70.5	-70.5	-70.0	-71.0	-70.0	-69.0	-70.5	-69.5	-69.0	-69.0	-69.0	-68.5	-68.0
256 QAM		-68.0	-67.5	-67.5	-67.0	-68.0	-67.0	-66.0	-67.5	-66.5	-66.0	-66.0	-66.0	-65.5	-65.0
512 QAM		-66.0	-65.5	-65.5	-65.0	-66.0	-64.5	-64.0	-65.5	-64.5	-64.0	-64.0	-64.0	-63.5	-63.0
1024 QAM (strong FEC)		-63.0	-62.0	-62.0	-62.0	-62.5	-61.5	-61.0	-62.0	-61.0	-60.5	-61.0	-60.5	-60.5	-59.5
1024 QAM (light FEC)		-62.0	-61.0	-61.0	-61.0	-62.0	-60.5	-60.0	-61.0	-60.5	-60.0	-60.0	-59.5	-59.5	-58.5
2048 QAM		-58.0	-57.5	-57.5	-57.0	-58.0	-56.5	-56.0	-57.5	-56.5	-56.0	-56.0	-56.0	-55.5	-55.0
QPSK	40 MHz	-86.0	-85.5	-85.5	-85.0	-86.0	-85.0	-84.0	-85.5	-84.5	-84.0	-84.0	-84.0	-83.5	-83.5
8 PSK		-81.0	-80.5	-80.5	-80.0	-81.0	-79.5	-79.0	-80.5	-79.5	-79.0	-79.0	-79.0	-78.5	-78.0
16 QAM		-79.5	-79.0	-79.0	-78.5	-79.5	-78.0	-77.5	-79.0	-78.0	-77.5	-77.5	-77.5	-77.0	-76.5
32 QAM		-76.0	-75.0	-75.0	-75.0	-75.5	-74.5	-74.0	-75.0	-74.0	-73.5	-74.0	-73.5	-73.5	-73.0
64 QAM		-73.0	-72.0	-72.0	-72.0	-73.0	-71.5	-71.0	-72.0	-71.5	-71.0	-71.0	-70.5	-70.5	-70.0
128 QAM		-70.0	-69.0	-69.0	-69.0	-70.0	-68.5	-68.0	-69.0	-68.5	-68.0	-68.0	-67.5	-67.5	-67.0
256 QAM		-67.0	-66.0	-66.0	-66.0	-66.5	-65.5	-65.0	-66.0	-65.0	-64.5	-65.0	-64.5	-64.5	-64.0

Modulation	Channel Size	Frequency (GHz)														
		6	7	8	10	11	13	15	18	23	24	26	28-31	32	38	
512 QAM	40 MHz	-64.0	-63.5	-63.5	-63.0	-64.0	-62.5	-62.0	-63.5	-62.5	-62.0	-62.0	-62.0	-61.5	-61.0	
1024 QAM (strong FEC)		-61.5	-61.0	-61.0	-60.5	-61.5	-60.0	-59.5	-61.0	-60.0	-59.5	-59.5	-59.5	-59.0	-58.5	
1024 QAM (light FEC)		-60.5	-60.0	-60.0	-59.5	-60.5	-59.5	-58.5	-60.0	-59.0	-58.5	-58.5	-58.5	-58.0	-58.0	
2048 QAM		-58.0	-57.0	-57.0	-57.0	-58.0	-56.5	-56.0	-57.0	-56.5	-56.0	-56.0	-55.5	-55.5	-55.0	
QPSK	50 MHz	-85.5	-84.5	-84.5	-84.5	-85.0	-84.0	-83.5	-84.5	-83.5	-80.0	-83.5	-83.0	-83.0	-82.5	
8 PSK		-80.0	-79.5	-79.5	-79.0	-80.0	-79.0	-78.0	-79.5	-78.5	-75.0	-78.0	-78.0	-78.0	-77.5	
16 QAM		-78.5	-77.5	-77.5	-77.5	-78.0	-77.0	-76.5	-77.5	-76.5	-73.0	-76.5	-76.0	-76.0	-75.5	
32 QAM		-74.5	-74.0	-74.0	-73.5	-74.5	-73.5	-72.5	-74.0	-73.0	-69.5	-72.5	-72.5	-72.5	-72.0	
64 QAM		-71.5	-70.5	-70.5	-70.5	-71.5	-70.0	-69.5	-70.5	-70.0	-66.0	-69.5	-69.0	-69.0	-68.5	
128 QAM		-68.5	-68.0	-68.0	-67.5	-68.5	-67.5	-66.5	-68.0	-67.0	-63.5	-66.5	-66.5	-66.5	-66.0	
256 QAM		-66.0	-65.0	-65.0	-65.0	-66.0	-64.5	-64.0	-65.0	-64.5	-60.5	-64.0	-63.5	-63.5	-63.0	
512 QAM		-63.5	-63.0	-63.0	-62.5	-63.5	-62.0	-61.5	-63.0	-62.0	-58.5	-61.5	-61.5	-61.5	-61.0	
1024 QAM (strong FEC)		-60.0	-59.5	-59.5	-59.0	-60.0	-58.5	-58.0	-59.5	-58.5	-55.0	-58.0	-58.0	-58.0	-57.5	
1024 QAM (light FEC)		-59.0	-58.0	-58.0	-58.0	-59.0	-57.5	-57.0	-58.0	-57.5	-53.5	-57.0	-56.5	-56.5	-56.0	
2048 QAM		-57.0	-56.0	-56.0	-56.0	-56.5	-55.5	-55.0	-56.0	-55.0	-51.5	-55.0	-54.5	-54.5	-54.0	
QPSK		56 MHz	-84.0	-83.5	-83.5	-83.0	-84.0	-83.0	-82.0	-83.5	-82.5	-82.0	-82.0	-82.0	-81.5	-81.5
8 PSK			-80.0	-79.5	-79.5	-79.0	-80.0	-79.0	-78.0	-79.5	-78.5	-78.0	-78.0	-78.0	-77.5	-77.5
16 QAM			-77.5	-77.0	-77.0	-76.5	-77.5	-76.5	-75.5	-77.0	-76.0	-75.5	-75.5	-75.5	-75.0	-75.0
32 QAM	-74.5		-73.5	-73.5	-73.5	-74.0	-73.0	-72.5	-73.5	-72.5	-72.0	-72.5	-72.0	-72.0	-71.5	
64 QAM	-71.0		-70.5	-70.5	-70.0	-71.0	-70.0	-69.0	-70.5	-69.5	-69.0	-69.0	-69.0	-68.5	-68.5	
128 QAM	-68.5		-67.5	-67.5	-67.5	-68.0	-67.0	-66.5	-67.5	-66.5	-66.0	-66.5	-66.0	-66.0	-65.5	
256 QAM	-65.0		-64.5	-64.5	-64.0	-65.0	-64.0	-63.0	-64.5	-63.5	-63.0	-63.0	-63.0	-62.5	-62.5	
512 QAM	-63.0		-62.5	-62.5	-62.0	-63.0	-61.5	-61.0	-62.5	-61.5	-61.0	-61.0	-61.0	-60.5	-60.0	
1024 QAM (strong FEC)	-59.5		-59.0	-59.0	-58.5	-59.5	-58.5	-57.5	-59.0	-58.0	-57.5	-57.5	-57.5	-57.0	-57.0	
1024 QAM (light FEC)	-58.5		-58.0	-58.0	-57.5	-58.5	-57.5	-56.5	-58.0	-57.0	-56.5	-56.5	-56.5	-56.0	-56.0	
2048 QAM	-54.0		-53.5	-53.5	-53.0	-54.0	-53.0	-52.0	-53.5	-52.5	-52.0	-52.0	-52.0	-51.5	-51.5	
QPSK	60 MHz		-84.5	-84.0	-84.0	-83.5	-84.5	-83.0	-82.5	-84.0	-83.0	-82.5	-82.5	-82.5	-82.0	-81.5
8 PSK			-80.0	-79.0	-79.0	-79.0	-79.5	-78.5	-78.0	-79.0	-78.0	-77.5	-78.0	-77.5	-77.5	-77.0
16 QAM			-77.5	-77.0	-77.0	-76.5	-77.5	-76.0	-75.5	-77.0	-76.0	-75.5	-75.5	-75.5	-75.0	-74.5
32 QAM		-74.0	-73.0	-73.0	-73.0	-73.5	-72.5	-72.0	-73.0	-72.0	-71.5	-72.0	-71.5	-71.5	-71.0	
64 QAM		-70.5	-70.0	-70.0	-69.5	-70.5	-69.5	-68.5	-70.0	-69.0	-68.5	-68.5	-68.5	-68.0	-68.0	
128 QAM		-68.0	-67.0	-67.0	-67.0	-67.5	-66.5	-66.0	-67.0	-66.0	-65.5	-66.0	-65.5	-65.5	-65.0	
256 QAM		-64.5	-64.0	-64.0	-63.5	-64.5	-63.5	-62.5	-64.0	-63.0	-62.5	-62.5	-62.5	-62.0	-62.0	
512 QAM		-62.5	-62.0	-62.0	-61.5	-62.5	-61.5	-60.5	-62.0	-61.0	-60.5	-60.5	-60.5	-60.0	-60.0	
1024 QAM (strong FEC)		-59.0	-58.5	-58.5	-58.0	-59.0	-58.0	-57.0	-58.5	-57.5	-57.0	-57.0	-57.0	-56.5	-56.5	
1024 QAM (light FEC)		-58.0	-57.5	-57.5	-57.0	-58.0	-57.0	-56.0	-57.5	-56.5	-56.0	-56.0	-56.0	-55.5	-55.5	
2048 QAM		-55.5	-54.5	-54.5	-54.5	-55.0	-54.0	-53.5	-54.5	-53.5	-53.0	-53.5	-53.0	-53.0	-52.5	
QPSK		80 MHz	-82.5	-82.0	-82.0	-81.5	-82.5	-81.5	-80.5	-82.0	-81.0	-80.5	-80.5	-80.5	-80.0	-80.0
8 PSK			-78.5	-78.0	-78.0	-77.5	-78.5	-77.5	-76.5	-78.0	-77.0	-76.5	-76.5	-76.5	-76.0	-76.0
16 QAM			-76.0	-75.5	-75.5	-75.0	-76.0	-75.0	-74.0	-75.5	-74.5	-74.0	-74.0	-74.0	-73.5	-73.5
32 QAM	-73.0		-72.0	-72.0	-72.0	-72.5	-71.5	-71.0	-72.0	-71.0	-70.5	-71.0	-70.5	-70.5	-70.0	
64 QAM	-69.5		-69.0	-69.0	-68.5	-69.5	-68.5	-67.5	-69.0	-68.0	-67.5	-67.5	-67.5	-67.0	-67.0	
128 QAM	-67.0		-66.0	-66.0	-66.0	-66.5	-65.5	-65.0	-66.0	-65.0	-64.5	-65.0	-64.5	-64.5	-64.0	
256 QAM	-63.5		-63.0	-63.0	-62.5	-63.5	-62.5	-61.5	-63.0	-62.0	-61.5	-61.5	-61.5	-61.0	-61.0	
512 QAM	-61.5		-61.0	-61.0	-60.5	-61.5	-60.0	-59.5	-61.0	-60.0	-59.5	-59.5	-59.5	-59.0	-58.5	
1024 QAM Strong	-58.0		-57.5	-57.5	-57.0	-58.0	-57.0	-56.0	-57.5	-56.5	-56.0	-56.0	-56.0	-55.5	-55.5	
1024 QAM Light	-57.0		-56.5	-56.5	-56.0	-57.0	-56.0	-55.0	-56.5	-55.5	-55.0	-55.0	-55.0	-54.5	-54.5	
2048 QAM	-54.0		-53.5	-53.5	-53.0	-54.0	-53.0	-52.0	-53.5	-52.5	-52.0	-52.0	-52.0	-51.5	-51.5	

ETHERNET THROUGHPUT

Modulation	Channel Size	Ethernet Throughput (Mbps)			Channel Size	Ethernet Throughput (Mbps)		
		No Compression	L2 Compression	Multi-Layer Compression		No Compression	L2 Compression	Multi-Layer Compression
QPSK	5 MHz	3	3-4	4-11	10 MHz	12	12-14	13-40
8 PSK		6	6-7	6-18		19	19-21	20-61
16 QAM		8	8-9	9-26		26	26-30	27-83
32 QAM		11	11-13	12-36		34	35-39	36-111
64 QAM		14	14-16	15-45		42	43-48	45-137
128 QAM		17	17-19	18-54		51	51-58	53-164
256 QAM		21	22-25	23-69		58	59-67	61-188
512 QAM		-	-	-		64	65-73	67-206
1024 QAM Strong		-	-	-		67	68-77	71-216
1024 QAM Light		-	-	-		72	72-82	75-230
QPSK	14 MHz	19	19-22	20-62	20 MHz	27	28-31	29-88
8 PSK		29	29-33	30-93		41	41-47	43-132
16 QAM		40	40-45	42-128		56	57-64	59-180
32 QAM		53	53-60	55-169		74	75-85	78-238
64 QAM		65	65-74	68-208		91	92-104	96-293
128 QAM		78	79-89	82-251		110	111-126	116-354
256 QAM		89	90-102	94-287		125	126-142	131-401
512 QAM		98	99-112	103-316		136	137-156	143-438
1024 QAM Strong		104	105-119	109-335		145	146-165	152-466
1024 QAM Light		111	111-126	116-355		154	155-176	162-495
2048 QAM	-	-	-	164	165-187	172-528		
QPSK	25 MHz	35	35-40	37-112	28 MHz	40	40-45	42-128
8 PSK		52	53-60	55-168		59	60-68	62-191
16 QAM		71	72-81	75-229		81	82-93	85-261
32 QAM		94	95-107	99-302		107	108-122	112-344
64 QAM		116	117-132	121-372		132	133-150	138-424
128 QAM		139	141-159	147-448		159	160-181	167-510
256 QAM		159	160-181	167-511		181	182-206	190-580
512 QAM		175	177-200	184-564		199	201-227	209-640
1024 QAM Strong		186	188-213	196-599		212	214-242	223-681
1024 QAM Light		198	199-226	208-636		225	227-257	236-723
2048 QAM	212	214-242	223-682	241	243-275	253-775		
QPSK	30 MHz	42	42-48	44-135	40 MHz	57	57-65	60-183
8 PSK		61	62-70	64-197		85	86-97	89-273
16 QAM		86	87-98	90-277		116	117-132	121-372
32 QAM		113	114-129	119-364		152	154-174	160-490
64 QAM		140	141-159	147-449		187	189-214	197-602
128 QAM		168	169-192	176-540		226	228-258	238-728
256 QAM		193	195-220	203-621		243	245-278	256-782
512 QAM		206	208-235	216-662		267	269-304	280-835
1024 QAM Strong	225	226-256	236-722	302	305-345	318-843		

PTP 820C SPECIFICATION SHEET

Modulation	Channel Size	Ethernet Throughput (Mbps)			Channel Size	Ethernet Throughput (Mbps)		
		No Compression	L2 Compression	Multi-Layer Compression		No Compression	L2 Compression	Multi-Layer Compression
1024 QAM Light	30 MHz	238	240-271	250-764	40 MHz	321	324-366	337-847
2048 QAM		260	262-296	273-833		347	350-396	365-853
QPSK	50 MHz	69	70-79	73-223	56 MHz	81	82-93	86-262
8 PSK		108	108-123	113-346		121	122-138	127-390
16 QAM		146	147-166	153-469		165	166-188	173-531
32 QAM		183	185-209	193-589		217	219-248	228-698
64 QAM		237	239-270	249-761		267	269-305	280-835
128 QAM		276	278-315	290-836		323	325-368	339-847
256 QAM		327	330-374	344-848		369	372-421	388-858
512 QAM		355	358-405	373-855		401	404-457	421-865
1024 QAM Strong		387	390-441	406-862		436	439-497	458-873
1024 QAM Light		411	414-468	431-867		462	466-528	486-879
2048 QAM		443	446-505	465-874		487	491-555	511-884
QPSK		60 MHz	86	86-98		90-276	80 MHz	113
8 PSK	125		126-143	131-402	160	161-183		168-515
16 QAM	174		175-198	182-558	228	230-260		240-733
32 QAM	229		230-261	240-734	300	302-342		315-841
64 QAM	281		283-320	295-837	367	369-418		385-857
128 QAM	339		342-387	356-851	433	436-494		455-872
256 QAM	391		394-447	411-863	499	503-569		524-887
512 QAM	421		424-480	442-869	548	552-625		576-898
1024 QAM Strong	458		461-522	481-878	596	601-680		626-909
1024 QAM Light	486		490-555	511-884	633	638-722		665-917
2048 QAM	527		531-601	553-894	670	675-762		703-926