

PMP 450i

Subscriber Module

Cambium Networks industry-leading 450 platform includes the all new PMP 450i and PTP 450i radios. The 450i product platform is the most scalable industrial-grade wireless broadband solution available.

QUICK LOOK:

- **Ultra-wide band radios: 5 GHz or 3 GHz**
- **Rugged metal enclosure**
- **2x2 OFDM MIMO radio capable of up to 300 Mbps per sector**



ULTRA-WIDE BAND RADIOS

Supports the entire band, whether in 5 GHz or 3 GHz. Advanced radio design improves transmit power and increases receive sensitivity.

RUGGED METAL ENCLOSURE

Designed to meet IP-66 and IP-67 standards to withstand harsh environments. Optional ATEX/HAZLOC certified models available for hazardous deployments.

DYNAMIC INTERFERENCE FILTERING

Provides industry-leading noise isolation for improved performance.

UPDATED FPGA AND SOC ARCHITECTURE

Triples the processing power compared to PMP 450.

MULTIFUNCTION AUX PORT

Allows for greater flexibility for deployment by adding a camera or other PoE directly.

OPTIONS FOR INTEGRATED 90° SECTOR ANTENNA

optimized for frequency re-use (>35 dB F/B), high gain, null fill and predictable performance, or Integrated 10° sector antenna for highly directional sectors.

INCREASE THROUGHPUT

Now capable of up to 300 Mbps per sector in a 40 MHz channel.

PMP 450i Subscriber Module

Product

		3 GHz	5 GHz
Model Numbers	Connectorized	C030045C001A	C050045C001B
	Integrated	C030045C002A	C050045C002C

Spectrum

Channel Spacing	Configurable on 2.5 MHz increments, 3 GHz customizable to 50 KHz		
Frequency Range	3 GHz: 3300 - 3900 MHz	5 GHz: 4900 - 5925 MHz	
Channel Width	5 MHz, 7 MHz, 10 MHz, 15 MHz, 20 MHz, 30 MHz or 40 MHz	5 MHz, 10 MHz, 15 MHz, 20 MHz, 30 MHz or 40 MHz	

Interface

MAC (Media Access Control) Layer	Cambium Networks proprietary
Physical Layer	2x2 MIMO OFDM
Ethernet Interface	100/1000BaseT, full duplex, rate auto negotiated (802.3 compliant)
Protocols Used	IPv4, IPv6, UDP, TCP/IP, ICMP, Telnet, SNMP, HTTP, FTP
Network Management	IPv4/IPv6 (dual stack), HTTP, HTTPS, Telnet, FTP, SNMPv2c and v3, Cambium Networks cnMaestro™
MTU	1700 bytes
VLAN	802.1ad (DVLAN Q-inQ), 802.1Q with 802.1p priority, dynamic port VID



PMP 450i Subscriber Module

Specifications

Performance

ARQ	Yes		
Modulation Levels (Adaptive)	MCS	Signal to Noise Required (SNR, in dB)	
2x	QPSK	10	
4x	16QAM	17	
6x	64QAM	24	
8x	256QAM	32	
Maximum Deployment Range	Up to 40 miles (64 km)		
Latency	3 - 5 ms, typical		
GPS Synchronization	Yes, via Autosync (CMM5 or UGPS)		
Quality of Service	Diffserve QoS		

Physical

Antenna Connection	50 ohm, N-Type (Connectorized version only)		
Surge Suppression (LPU fitted)	EN61000-4-5: 1.2us/50us, 500 V voltage waveform Recommended external surge suppressor: Cambium Networks Model # C000000L033A		
Mean Time Between Failure	>40 Years		
Dust and Water Ingress Protection Rating	IP67, IP66		
Temperature / Humidity	-40°C to +75°C (-40°F to +167°F), 0-100% condensing		
Weight	Connectorized	Approx. 2.0 kg (4.5 lbs)	
	Integrated	Approx. 2.5 kg (5.5 lbs)	
Wind Survival	322 km/h (200 mi/h)		
Vibration	NEMA TS2 Section 2.1.9 and Section 2.2.3		
Shock	NEMA TS2 Section 2.1.10 and Section 2.2.4		
External Icing	NEMA 250-2003 Section 5.6		
Dimensions (HxWxD)	Connectorized	26.0 x 13.4 x 6.4 cm (10.25" x 5.25" x 3.25")	
	Integrated	31.0 x 31.0 x 6.4 cm (12" x 12" x 2.5")	
Power Consumption	15 W typical, 18 W max, Using Aux port PoE for another device will increase power draw		
Input Voltage	48-59 V DC, 802.3at compliant		
Mounting	Wall or Pole mount with Cambium Networks Model # N000045L002A		

PMP 450i Subscriber Module

Link Budget

	3 GHz	5 GHz
Antenna Beam Width	17° azimuth for integrated antenna	10° azimuth for integrated antenna
Antenna Gain	+19 dBi dual slant integrated, or external	+23 dBi H+V integrated, or external
Maximum Transmit Power	+25 dBm (MIMO, Combined H+V)	+28 dBm (MIMO, Combined H+V) (may be limited by regulations)
Maximum EIRP	+43 dBm combined output (may be limited by regulations)	+50 dBm combined output (may be limited by regulations)
Power Control	ATPC (Automatic Transmit Power Control) at system level, all Subscribers implement ATPC	

Security

3 GHz / 5 GHz

Encryption	FIPS-197 128-bit AES, 256-bit AES (<i>Requires Optional License</i>)
-------------------	---

Certifications

	3 GHz	5 GHz
ISED Canada	109W-0028 (3 GHz)	109AO-50450I (4.9, 5.2, 5.4, 5.8 GHz)
FCC ID	Z8H89FT0028 (3 GHz)	QWP-50450I (4.9, 5.1, 5.2, 5.4, 5.8 GHz)
CE	EN 302 326-2 v1.2.2 (3 GHz)	EN 301 893 v1.8.1 (5.4 GHz) <hr/> EN 302 625 v1.11 (Broadband Disaster Relief, 4.9 GHz, 5.1 GHz) <hr/> EN 302 502 v1.2.1 (5.8 GHz)

ABOUT CAMBIUM NETWORKS

Cambium Networks empowers millions of people with wireless connectivity worldwide. Its wireless portfolio is used by commercial and government network operators as well as broadband service providers to connect people, places and things. With a single network architecture spanning fixed wireless and Wi-Fi, Cambium Networks enables operators to achieve maximum performance with minimal spectrum. End-to-end cloud management transforms networks into dynamic environments that evolve to meet changing needs with minimal physical human intervention. Cambium Networks empowers a growing ecosystem of partners who design and deliver gigabit wireless solutions that just work.